

SPECIFICATION

BE IT KNOWN THAT

DIANE E. DELANEY

a citizen of the United States of America, residing at 2408 Route 32, New Windsor,
New York 12553; and

CORNELIA A. ARNDT

a citizen of the United States residing at P.O. Box 24, Pine Bush, New York 12566

have invented new and useful improvements in a

METHOD AND APPARATUS FOR DRYING NAILS

of which the following is a specification:

METHOD AND APPARATUS FOR DRYING NAILS

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to nail drying. More ,specifically this

5 invention relates to an apparatus and a method for completely drying nail polish using both warm and very cold air.

Description of the Prior Art

In nail and beauty salons, one of the substantial sources of income is manicures

10 and pedicures, i.e. the cleaning, toning and polishing of the fingernails and toenails.

One of the problems inherent in the process is that clients have limited time after the nails are polished. The client normally waits at the salon for about fifteen to twenty

minutes hoping to dry her nails at room temperature. However, the nails are not

completely dry after that time frame. Invariably, the customer nicks or smudges the

15 nails after leaving the salon. As a result, the damaged nails must be redone and still

more time is spent waiting for the nail polish to dry. Many manicurists do not utilize

machines to assist in drying fingernails or toenails after a polish is applied. However,

nail drying machines are well known in the art. Such devices fail to reduce the drying

time for nails to an appreciable extent.

20 Existing apparatus to dry nails can be broken down into three categories.

Category one includes nail polish dryers that utilize heat. Examples of such nail polish dryers are as follows:

PATENTEE	US PATENT NUMBER
GOODMAN	2,184,858
FINGERLIN	2,262,274
NEMETH	2,734,282
5 SELDITZ	3,287,824
FRIEDMAN ET AL	3,864,847
SIGMAN	4,255,871

Category two uses forced ambient air to dry nails. However, in this group the ambient air is not heated or cooled by external means. The Simmons Patent, US Patent 2,389,822 shows a nail polish dryer where separate finger receiving passages are provided for each finger and the thumb. Air is directed past the tips of the fingers and is vented from the device by outlets. US Patent 4,193,209 is a nail dryer that equips the device with a hand rest to aid in both the application of the polish and that is positioned such that air is driven by a fan and deflected by the vents which speeds the drying of the polish. The Duchoud Patent, US Patent 5,084,984 is a clamshell type of housing where the device is opened by tilting the cover back on its hinges and contact strips are brought together providing power to a fan that drives air through the drying zone. Opening the cover activates the fan which supplies air to dry the nails.

Category three includes patents which use cooled air to dry nails. The Outlaw Patent, US Patent 4,464,906, uses air that is cooled below ambient temperatures before it is directed onto the fingernails. In this patent, the temperature discussed is between forty-five and sixty-five degrees Fahrenheit.

In general, the main problem with conventional nail polish drying machines is that they don't dry or set the nails completely. This is evidenced in the Edelman Patent, US Patent 5,280,679 whereby the inventor claims that she can dry nails to a "substantial" state. Drying to a "substantial state" means that the nails are not completely dried and therefore will smudge or nick. Also, the prior art states that optionally it would be possible to further augment the speed of the drying process by utilizing a chemical drying agent. This further highlights the major weakness of the prior art machines because if such machines worked, there would be no need for additional chemical drying agents.

It is apparent that there is a clear need for a method of drying nails and an apparatus to perform that method which results in a hardened finish.

OBJECTS OF THE INVENTION

The objects of this invention are as follows:

To provide for quick drying of nail polish;

To provide a method and apparatus for drying nails that produces a completely hardened nail polish that will not smudge or nick;

To sanitize the apparatus after each use;

To provide a nail dryer that will dry both hands or both feet at one time;

To provide a nail dryer that will dry nails in a brief time period of no more than six minutes;

To provide a nail dryer that is compact and easy to use and completely automatic;

To provided a nail dryer that will completely dry nails to total dryness;

To provide an apparatus for drying nails which is inexpensive and dependable;

To provide for quick and complete drying of nail polish by providing a warm and
very cold temperature in the area proximate to the polished nail within a time of less
5 than seven minutes.

These and other objects of the present invention will become readily apparent
upon further review of the following specifications and drawings;

SUMMARY OF THE INVENTION

A method is provided for drying nail polish that has been applied to the nails of
10 an extremity. First, warm air is directed on the nails and hen followed by very cold air.

An apparatus is also provided to perform the above method. The apparatus
which works with a power supply includes a housing with an opening in it into which an
extremity is placed. A means for heating and cooling air including a means for directing
the means for heating and cooling air to blow first warm air and then very cold air on the
15 extremities. Preferably, a sanitizing means for sanitizing the enclosure and a means for
activating the sanitizing means are also provided.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic view showing the steps of the method in accordance
with this invention.

20 Fig. 2 is a perspective view of the outside enclosure of the apparatus in
accordance with this invention.

Fig. 3 is an internal top view of the placement of the components of this invention and showing a hand within the apparatus.

Fig. 4 is a block diagram of the electrical components of the apparatus.

BRIEF DESCRIPTION OF THE NUMERALS

	NUMERAL	DESCRIPTION
5	11	EXTREMITY
	12	FLOW OF AIR
	13	HOUSING
	14	MOTOR AND FAN
10	15	TEMPERATURE SETTING UNIT
	17	TEMPERATURE CONTROLLER
	19	BASE
	20	TOP
	21	TWO SIDE PANELS
15	23	FRONT AREA
	25	BACK PANEL
	27	FRONT PANEL
	29	OPENING
	31	MOTION SENSOR
20	33	ENCLOSURE
	35	POWER SWITCH
	37	SANITIZING BULB

39	POWER SUPPLY
41	REST PLATE
45	AIR HEATER AND COOLER
51	HOT AND COLD TIMERS
55	TEMPERATURE SENSOR
57	LOGIC CIRCUIT
59	BULB TIMER

DESCRIPTION OF THE PREFERRED EMBODIMENT

The invention provides an improved method and an apparatus for completely drying the polish applied to nails. As used herein, the term polish encompasses different liquids normally applied to the nails by a manicurist. Each of these materials is in liquid form when applied to the nails and the nail is therefore "wet" until the liquid has dried and hardened to the extent that it can no longer be removed by merely touching the nail against an object. It will be understood that the phrase "drying the nails" as used herein means completely drying the polish on the nails. Additionally, it will be understood that the phrase completely dry" as used herein, means with no incidence of any wetness to permit smudging or nicking of the polish.

The present invention involves the use of warm and very cold air to dry the polish on the nails. It has been found that the combined sequential use of warm and very cold air dries polish more quickly than room temperature air or either just warm air or very cold air.

Referring to FIG 1, the three steps of the method are shown. An extremity 11, which may be either hands or feet having freshly polished nails, is placed in a flow of air 12.

In Step one, warm air having a temperature range of eighty-three to eighty-five degrees Fahrenheit, is blown on the newly polished nails. The preferred temperature is 5 eighty-five degrees Fahrenheit . The warm air is applied for approximately four minutes.

Then, as shown is Step Two of FIG 1, the air is cooled to a range of thirty-four to thirty-five degrees Fahrenheit and blown on the nails for two minutes.

At the conclusion of Step Two of FIG 1, as shown in Step Three, the temperature 0 of the air being blown into the nails is once again increased to the range of eight-three to eighty-five degrees Fahrenheit for a very brief period, namely approximately fifteen seconds. Complete drying can be obtained without Step Three but comfort is obtained by Step Three.

The above described method is provided by an apparatus shown in FIG 2. This 15 apparatus is suitable for use at one's home or in a manicurist's salon directing warm and very cold air, in accordance with the described method, onto newly polished nails.

In FIG 2, the apparatus is shown for producing the previously described method. A housing 13 is provided in which a motor and fan 14, a temperature setting unit 15 and a temperature controller 17. The housing 13 includes a base 19, a top 20, two side 20 panels 21, a front area 23 , a back panel 25 and a front panel 27. An opening 29 is located in the front area 23 of the housing 13 for insertion of extremities, namely,

hands or feet, as may be desired. The nail dryer is designed for the insertion of both extremities 11, whether two hands or two feet, at the same time.

The opening 29 is where the extremities 11 are inserted to obtain nail drying. A motion sensor 31 is located in an enclosure 33. The opening 29 provides access to the enclosure 33 within the housing 13. A power switch 35 turns the nail dryer on and off. A sanitizing bulb 37 is also located in the enclosure 33. The motion sensor 31, providing the power switch 35 is on, upon an extremity 11 or pair of extremities 11 being placed into the enclosure 33 activates the commencement of the nail drying process. The nail dryer, must of course, be connected to a power supply 39.,

A rest plate 41 onto which the extremities 11 are placed within the enclosure 33 is located slightly higher than the base 19 of the housing 13. The rest plate 41 preferably has a non-porous, skid free surface. The front panel 27 drops down to a level approximately four inches above the rest plate when an extremity is placed on the rest plate 41. The front panel 27 retracts at the end of the drying cycle and is activated by the motion sensor 31 located within the housing 13 which would sense loss of air movement. The front panel 27 must retract before the extremities are removed so there will be no chance of hitting the nails on the front panel 27. Once the front panel 27 has retracted, free movement is provided to retract the extremities.

The power supply 39 is connected to the motor and fan 14 and an air heater and cooler 45 and to the temperature controller 17. There is no need for further external control adjustment means because the nail dryer operates through the temperature controller 17 and a warm and very cold time 47.

Figure 3 shows a top view of the lower portion of the enclosure 33. An extremity 11 with nails requiring drying of polish is shown inserted into the opening 29 and placed upon the rest plate 41. The motion sensor 31 detects the presence of the extremity 11 which has been inserted into the opening 29. Toward the back panel 25 of the housing 11, an air heater and cooler 45 is located. The air heater and cooler 45 contains the motor and fan 14. The air forced by the motor and fan 14 which passes through the air heater and cooler 45 is directed at the extremities 11 on the rest plate 41.

Also located with the air heater and cooler 45 are the temperature controller 17, hot and cold timers 51, temperature setting unit 53 for both hot and cold temperatures, and a temperature sensor 55.¹ The enclosure 33 of the nail dryer also contains the sanitizing bulb 37. This sanitizing bulb 37 turns on for a preset period of time when the motion sensor 31 detects that the extremities 49 have been removed from the nail dryer.

FIG. 4 shows a block diagram of the electrical components of the nail dryer. As previously stated, the motion sensor 31 detects the insertion of an extremity 11 into the nail dryer. When this insertion occurs, the motion sensor 31 generates an "On" signal, which goes to the temperature controller 17 to indicate that the warm-very cold-warm drying cycle should begin. The temperature controller 17 then begins generating the warm cycle, which needs to be active for four minutes. The warm and very cold timers 51 control the length of this period, which as the method states, is four minutes. The

¹ Thermo-electric modules, including Temperature Controllers and related equipment for producing alternating warm and very cold air flows are commercially available from TE Technology, Inc., 1590 Kenine Drive, Traverse City, MI 49686-8257.

temperature controller 17 sends an output of a specified polarity to the air heater and cooler 45 during the warm period. The proper polarity for triggering a warm air output from the air heater and cooler 45 is established by a logic unit 57. After the initial warm period, the temperature controller 17 shifts into the very cold period, which extends for two minutes as directed by the hot and cold timers 51. The proper polarity for triggering a very cold air output from the air heater and cooler 51 is established by the logic unit 57. The temperature controller 17 provides an output that is inverted for a very cold cycle. The temperature controller 17 gets its warm and very cold temperatures for the warm and very cold temperatures periods from the temperature setting unit 15.

The temperature sensor 55 measures the temperature of the ambient air inside the nail dryer to regulate and maintain that ambient temperature at a stable eighty-five degrees Fahrenheit for warm periods and thirty-five degrees Fahrenheit for very cold periods. The power supply 39 supplies the required electricity for all of the electrical components shown in FIG. 4.

FIG. 4 also shows the sanitizing bulb 37, which is an ultraviolet germicidal light bulb and is turned on by the motion sensor 31 when the extremity 49 is removed from the enclosure. The sanitizing bulb 37 stays on for a period of time dictated by a bulb timer 59.

The advantages of this invention are several. It is the primary advantage of the present invention to have a combination of warm and very cold air to enable polished nails to dry completely, avoiding the need to immediately repeat the application of nail polish. Another advantage is to provide a machine that will dry nails more quickly than

prior art machines. The provision for a sanitized rest plate for each client is most advantageous. The nail dryer provides a completely automated approach for the user. With this invention, time is saved for the nail salon owner, as the whole drying and sanitizing process is automatic, so operators do not have to oversee the individual client nail drying process .

It is to be understood that the drawings and description matter are in all cases to be interpreted as merely illustrative of the principles of the invention, rather than as limiting the same in any way, since it is contemplated that various changes may be made in various elements to achieve like results without departing from the spirit of the invention or the scope of the appended claims.